



OAR02-010 OUTDOOR ACTIVE REPEATER (10Watts)

- **Broadband Repeater with 31 Channel Capability**
- **Upgradeable to Higher Power Repeaters**
- **High Power Amplifier**
- **Durable Construction**
- **Efficient, Compact Size**
- **Digital Ready**

PRODUCT APPLICATION:

The OAR02-010 is a solid-state, broadband, on-frequency repeater designed to receive, amplify, and retransmit up to 31 analog television channels or 150 digital channels (64QAM modulation).

The OAR02-010 is designed to provide cost-effective coverage over a small area.

With an omnidirectional transmit antenna it can cover an area of approximately 2.1 Kilometer radius when fully loaded with 31 channels or a 3.1 Km radius when loaded with 15 channels. A larger area can be covered if the desired coverage is less than 360 degrees in azimuth.

The per channel output power depends on the channel loading. For a 12 channel load, the repeater delivers a total of over 32 MW per channel with a C/CTB of 50 dB (measured with CW carriers).

The OAR02-010 is designed to operate outdoors in a variable temperature environment. For increased reliability, an external cooling heatsink maintains component temperatures at desirable levels and an internal temperature sensor protects the high power amplifier from failure due to overheating.

To facilitate operational monitoring with a field strength meter or a TV monitor, the OAR02-010 includes a test point connector.

Operational diagnostic voltages can be monitored locally. An option allows the voltages to be monitored remotely via serial port interface to a standard Windows equipped PC.

The repeater features an efficient, compact design, consisting of a Microwave AGC circuit, a Low Noise Amplifier (LNA), and a Power Amplifier, all packaged in a weather proof enclosure.

Product Specification¹

CABLE AML

Repeater																			
Input Frequency ² :	2.5 to 2.7 GHz																		
Nominal Input Level for 12 TV:	-45 dBm/ch																		
Output Frequency ² :	2.5 to 2.7 GHz																		
Output Level for 50 dB C/CTB: (measured with CW carriers) ³	<table border="1"><thead><tr><th>Channels</th><th>Average Power dBm/Channel</th><th>Peak Power dBm/Channel</th></tr></thead><tbody><tr><td>9</td><td>17.5</td><td>20.0</td></tr><tr><td>12</td><td>16.0</td><td>18.5</td></tr><tr><td>18</td><td>14.0</td><td>16.5</td></tr><tr><td>24</td><td>12.0</td><td>14.5</td></tr><tr><td>30</td><td>11.0</td><td>13.5</td></tr></tbody></table>	Channels	Average Power dBm/Channel	Peak Power dBm/Channel	9	17.5	20.0	12	16.0	18.5	18	14.0	16.5	24	12.0	14.5	30	11.0	13.5
Channels	Average Power dBm/Channel	Peak Power dBm/Channel																	
9	17.5	20.0																	
12	16.0	18.5																	
18	14.0	16.5																	
24	12.0	14.5																	
30	11.0	13.5																	
Frequency Response:	±1 dB																		
Gain:	56 dB min.																		
Noise Figure:	5 dB																		
Input Return Loss:	15 dB																		
Input Connector:	Type "N"																		
Output Return Loss:	18 dB																		
Output Connector:	Type "N"																		
Temperature Range:	-40° to 122°F (-40° to 50°C)																		
Primary Power:	60/120/240 VAC @ 50/60Hz (per customer spec)																		
Power Consumption:	250 WATTS																		
Mounting:	Antenna Pole																		
Weight:	40 lb. (18.2 kg)																		
Dimensions:	13" W x 7.5"H x 24"D (33 x 19 x 61 cm)																		

¹ Specifications subject to change without prior notice.

² Other frequencies available.

³ The C/CTB with modulated carriers are approximately 6 dB better than with CW carriers.