

OAR02-250 OUTDOOR ACTIVE REPEATER (250 Watts)



- **Broadband High Power Repeater**
- **31 Analog Channels or 150 Digital TV Programs**
- **Outdoor Mounting to Minimize Waveguide Losses**
- **Built-in VHF Monitoring Ports**
- **Efficient, Compact Design**

PRODUCT APPLICATION:

The OAR02-250 is a broadband, on frequency repeater designed to receive, amplify, and retransmit up to 31 analog television channels or 150 digital channels (64 QAM, 256 QAM or OFDM modulation).

The OAR02-250 is designed to provide cost effective coverage over a wide area. With an omnidirectional transmit antenna it can cover an area of approximately 24 Kilometer radius when fully loaded with 31 channels, or a 35 km radius when loaded with 15 channels. A larger area can be covered if the desired coverage is less than 360 degrees in azimuth.

The output power per channel depends on the number of channels. For 31 channels the repeater delivers a peak power of over 200 milliwatts per channel with a C/CTB of 50 dB.

The OAR02-250 is designed to operate outdoors in a variable temperature environment.

For increased reliability, an external cooled heatsink maintains component temperatures at desirable levels and an internal temperature sensor protects the high power amplifier from failure due to overheating.

To facilitate operational monitoring with a field strength meter or a TV monitor, the OAR02-250 includes optional input/output VHF monitors.

Operational diagnostic voltages can be monitored locally. An option allows the voltages to be monitored remotely via serial port interface to a standard Windows- equipped PC.

The repeater features an efficient, compact design, consisting of a Microwave AGC circuit, a Low Noise Amplifier (LNA), and a Power Amplifier, all packaged in a weather-proof enclosure.

Repeater																			
Input Frequency ² :	2.5 to 2.7 GHz																		
Nominal Input Level for 12 TV:	-45dBm																		
Output Frequency ² :	2.5 to 2.7 GHz																		
Output Level for 50 dB C/CTB: (measured with CW carriers) ³	<table border="1"> <thead> <tr> <th>Channels</th> <th>Average Power dBm/Channel</th> <th>Peak Power dBm/Channel</th> </tr> </thead> <tbody> <tr> <td>9</td> <td>31.5</td> <td>34.0</td> </tr> <tr> <td>12</td> <td>30.0</td> <td>32.5</td> </tr> <tr> <td>18</td> <td>28.0</td> <td>30.5</td> </tr> <tr> <td>24</td> <td>26.0</td> <td>28.5</td> </tr> <tr> <td>30</td> <td>25.0</td> <td>27.5</td> </tr> </tbody> </table>	Channels	Average Power dBm/Channel	Peak Power dBm/Channel	9	31.5	34.0	12	30.0	32.5	18	28.0	30.5	24	26.0	28.5	30	25.0	27.5
Channels	Average Power dBm/Channel	Peak Power dBm/Channel																	
9	31.5	34.0																	
12	30.0	32.5																	
18	28.0	30.5																	
24	26.0	28.5																	
30	25.0	27.5																	
Local Oscillator Frequency ² :	±1 dB																		
Gain:	66 dB min.																		
Noise Figure:	5 dB																		
Input Return Loss:	15 dB																		
Input Connector:	Type "N"																		
Output Return Loss:	18 dB																		
Output Connector:	Type "N"																		
Temperature Range:	-40° to 122°F (-40° to 50° C)																		
Primary Power:	60/120/240 VAC @ 50/60 Hz (per customer spec)																		
Power Consumption:	1050 VA RMS																		
Mounting:	Antenna Pole																		
Weight:	160 lbs (72.5 kg)																		
Dimensions:	24" W x 24" H x 15" D (61cm x 61cm x 38.1cm)																		

¹ Specifications subject to change without prior notice.

² Other frequencies available.

³ The C/CTB with modulated carriers are approximately 6 dB better than with CW carriers.