

ITX-002 INDOOR BROADBAND TRANSMITTER



- **Broadband Transmitter with 80 Channel Capability**
- **Can Feed One Link of 6 Miles or Four Links of 3 Miles each with 40 Channel Loading**
- **Upgradeable, Modular Design**
- **Requires only 7 inches of Indoor Rack Space**
- **Digital Ready**

PRODUCT APPLICATION:


The ITX-002 is a solid state broadband transmitter designed to implement high quality, cost-effective microwave links for transporting up to 80 television channels.

This transmitter can be used to feed a single link or several links simultaneously. A typical application example would be a single 6-mile (10 kilometer) link with 40 channel loading, or 4 simultaneous links of 3 miles (5 kilometers) each.

The ITX-002 is rack mounted for convenience and ease of access to components. It incorporates the latest Gallium Arsenide power amplifier technology to deliver a clean, reliable signal.

Output signal monitoring and diagnostic measurements are available locally or remotely via Internet.

Designed for many years of trouble-free operation, the ITX-002 can be field upgraded to higher power units of the ITX solid state family of transmitters.



ITX-002

Transmitter																			
Input Frequency ² :	54 to 550 MHz																		
Nominal Input Level for 12 TV:	+10 dBmV (-39 dBm per channel)																		
Output Frequency ² :	12.7 to 13.25 GHz																		
Output Level for 65 dB C/CTB:	<table border="1"> <thead> <tr> <th>Channels</th> <th>dBm/Channel</th> <th>C/N (dB)</th> </tr> </thead> <tbody> <tr> <td>12</td> <td>-1.0</td> <td>61.0</td> </tr> <tr> <td>21</td> <td>-3.4</td> <td>58.5</td> </tr> <tr> <td>35</td> <td>-6.0</td> <td>56.0</td> </tr> <tr> <td>60</td> <td>-8.5</td> <td>53.5</td> </tr> <tr> <td>80</td> <td>-9.5</td> <td>52.5</td> </tr> </tbody> </table>	Channels	dBm/Channel	C/N (dB)	12	-1.0	61.0	21	-3.4	58.5	35	-6.0	56.0	60	-8.5	53.5	80	-9.5	52.5
	Channels	dBm/Channel	C/N (dB)																
	12	-1.0	61.0																
	21	-3.4	58.5																
	35	-6.0	56.0																
	60	-8.5	53.5																
80	-9.5	52.5																	
Normal Gain ³ :	33 dB																		
Frequency Response:	±1 dB																		
Frequency Stability:	0.0005%																		
Input Return Loss:	15 dB																		
Input Connector:	Type "F"																		
Output Return Loss:	18 dB																		
RF Output Connector:	WR-75 Waveguide																		
Temperature Range:	60° to 100°F (16° to 32°C)																		
Humidity	95% max.																		
Primary Power:	120 VAC, 50/60Hz																		
Power Consumption:	250 VA RMS																		
Mounting:	19" EIA Standard Relay Rack																		
Weight:	30.0 lb. (13.6 kg)																		
Dimensions:	19" W x 7" H x 20" D (48.26cm W x 17.78cm H x 50.88cm D)																		

¹ Specifications subject to change without prior notice.

² For Group C. Other frequencies available.

³ Gain may be varied with 10dB attenuator.