

## **BST26-001 BROADBAND BASE STATION TRANSCEIVER**

- **Solid-State Design for LMDS Applications**
- **Compact Outdoor Package**
- **QPSK, QAM or COFDM Capability**
- **Single Antenna for Transmit and Receive**



### **PRODUCT APPLICATION:**

The BST26-001 is a solid-state transceiver designed to provide P-T-MP (point-to-multi-point), full duplex (two-way) communication with QPSK, QAM or COFDM modulated carriers (FDMA multiple carrier regime) in the 28 GHz frequency band.

The BST26-001 consists of an outdoor transceiver and an indoor Interface Processing Unit (IPU). The outdoor transceiver features a modular design consisting of integrated transmitter, receiver and diplexer modules. The high-performance diplexer makes it possible to use the transceiver with a single antenna. The outdoor transceiver package is mechanically integrated with the antenna to provide a low-loss connection and to facilitate installation, mounting and antenna aligning.

The indoor IPU is a rack mounted chassis that provides frequency conversion, reference oscillator, and AC power to the outdoor transceiver. Downstream transmission is in the 26.5-28.5 GHz band and upstream reception is in the 29.0-31.0 GHz band.

The transceiver is offered with an output power capability of 1 watt (1-dB Compression Point of +30 dBm).

Test points are provided to monitor output signal level, IF input levels and crystal oscillator reference frequency. Diagnostic voltages are provided for local or remote monitoring.

# Product Specification<sup>1</sup>

# CABLE AML

<b>Transmitter Section</b>	
Input Frequency <sup>2</sup> :	Downstream: 950 - 1450 MHz
Modulation Format:	QPSK, 16-QAM, 64-QAM, COFDM
Input Level per carrier (nominal):	-30 dBm/carrier
Output Level:	27 dBm max (Single QPSK Carrier)
Output Frequency <sup>2</sup> :	26.5 - 28.5 GHz
<b>Receiver Section</b>	
Input Frequency <sup>2</sup> :	29.0 - 31.0 GHz
Noise Figure:	6 dB
Output Level (Nominal):	-20 dBm
Output Frequency <sup>2</sup> :	400 - 700 MHz
<b>Common Specifications</b>	
Frequency Response:	±1 dB
Frequency Stability:	± 2 ppm
Input Return Loss:	15 dB
Output Return Loss:	18 dB
RF Connectors:	WR-28 Waveguide
Input/Output Connector:	Type "N"
Mounting:	Outdoor mount to vertical pipe
Temperature Range:	-40° to 113°F (-40° to 45°C)
Humidity:	100%
Primary Power:	110/220 VAC, 50/60Hz (per customer specification)
Weight:	10 lb. (4.5 kg)
Dimensions:	20cmW x 20cmH x 15cmD (8" x 8" x 6")

<sup>1</sup> Specifications subject to change without prior notice.

<sup>2</sup> Other frequencies available.